

LA 60S-TU

Heat output / coefficient of performance (COP) according to EN 14511:1)

Heizen 1 Verdichter	W35	W45	W55
A-15	16.9 kW / 2.6		
A-7	22.2 kW / 3.2		
A2	26.6 kW / 3.6		
A7	35.3 kW / 4.5	32.9 kW / 3.7	31.7 kW / 3.2
A12	38.1 kW / 4.8		
A20			
Heizen 2 Verdichter	W35	W45	W55
A-15	31.7 kW / 2.6		
A-7	38.0 kW / 3.0		
A2	43.4 kW / 3.4		
A20			

Note:

1) This data indicates the size and capacity of the system according to EN 14511. For an analysis of the economic and energy efficiency of the system, the bivalence point and regulation should be taken into consideration. These specifications can only be achieved with clean heat exchangers. Information on maintenance, commissioning and operation can be found in the respective sections of the installation and operating instructions. The specified values have the following meaning, e.g. A7 / W35: Heat source temperature 7 °C and heating water flow temperature 35 °C.




Glen Dimplex Thermal Solutions
(Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100
Am Goldenen Feld 18 F: + 49 9221 709-339
D-95326 Kulmbach dimplex@dimplex.de
www.dimplex.de

Glen Dimplex Austria GmbH
Hauptstraße 71
A-5302 Henndorf am Wallersee
info@dimplex.at
www.dimplex.at

T: + 43 6214 20330
F: + 43 6214 203304
info@dimplex.at
www.dimplex.at

LA 60S-TU

Heating water temperature [°C]



Heat source inlet temperature [°C]

Note:
The maximum possible flow temperature and the operating limits vary by +/- 2K due to component tolerances.
The minimum volume flow specified in the device information must be ensured at the lower operating limit.
In mono energy operating mode with the heating element activated, the maximum flow temperature increases by approximately 3K.



Glen Dimplex Thermal Solutions T: +49 9221 709-100
(Glen Dimplex Deutschland GmbH) F: +49 9221 709-339
Am Goldenen Feld 18 dimplex@dimplex.de
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: +43 6214 20330
Hauptstraße 71 F: +43 6214 203304
A-5302 Henndorf am Wallersee info@dimplex.at
www.dimplex.at