



Data sheet WI 22TU

High efficiency water-to-water heat pump for indoor installation.

Installation location:

Max. flow temperature: 62 °C

Casing colour: White (similar to RAL 9003)

Heat pump for heating purposes for indoor installation with integrated heat pump manager WPM Econ5Plus with touch display. Variable connection options for the ground water and heating connections on the rear wall of the casing. Integrated solid-borne sound insulation for direct connection to the heating system. Sound-optimised through encapsulated compressor housing and free-swinging compressor baseplate. High coefficients of performance (COPs) thanks to electronic expansion valve, COP booster and compliance with the requirements of EN 14511 for larger volume flows on the heat consumption side. Integrated corrosion-proof and freeze-proof stainless steel coil evaporator. Sensor monitoring of the refrigeration circuit for a high degree of operational safety and integrated thermal energy metering (display of the calculated quantity of thermal energy for heating and domestic hot water preparation on the heat pump manager). If the evaporation temperatures are too low, e.g. due to an inadequate water flow, the heat pump switches off, which means that no flow rate switch is required. For well systems with an insecure water supply, a flow rate switch available as a special accessory can also be installed. Universal design for low-temperature heating systems with flexible expansion options for:

- Room temperature control via Smart RTC (special accessory)
- Bivalent or bivalent-renewable operating mode
- Distribution systems with unmixed and mixed heating circuits
- Use of load-variable tariffs (SG Ready)

Integrated soft starter (from WI 14); integrated load contactor for well water pump; flow sensor, return sensor, external sensor (standard NTC-2) and dirt filter for ground water included in the scope of supply. Heat pump white textured (similar to RAL 9003).



Glen Dimplex Thermal Solutions
(Glen Dimplex Deutschland GmbH) T: +49 9221 709-100
Am Goldenen Feld 18 F: +49 9221 709-339
D-95326 Kulmbach dimplex@dimplex.de
www.dimplex.de

Glen Dimplex Austria GmbH
Hauptstraße 71
A-5302 Henndorf am Wallersee
T: +43 6214 20330
F: +43 6214 203304
info@dimplex.at
www.dimplex.at

WI 22TU

Technical data

Dimplex High efficiency water-to-water heat pump for indoor installation. (Medium temperature)

Heat pump code	3007
Max. flow temperature	62 Grad
Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation)	7 Grad / 25 Grad
Sound power level	47 dB(A)
Refrigerant / Amount of refrigerant	R410A / 4,0 kg
Max. heating water flow rate / Pressure drop	3,8 m3 pro h / 22900 Pa
Heat source flow (min.)	4,0 m3 pro h
Width x Height x Depth **	650 x 845 x 665 mm
Weight	179 kg
Rated voltage	3/PE ~400 V, 50 Hz
Starting current	28 A
Heat pump seal of approval (valid until)	Yes / 12.12.2020

*Heat output and coefficient of performance (COP) according to EN 14511

**Please note that additional space is required for pipe connections, operation and maintenance.



Glen Dimplex Thermal Solutions
(Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100
Am Goldenen Feld 18 F: + 49 9221 709-339
D-95326 Kulmbach dimplex@dimplex.de
www.dimplex.de

Glen Dimplex Austria GmbH
Hauptstraße 71
A-5302 Henndorf am Wallersee
info@dimplex.at
www.dimplex.at

T: + 43 6214 20330
F: + 43 6214 203304
info@dimplex.at
www.dimplex.at

WI 22TU

Description	Order ref.	Article number	Sample item	Item
Heat pumps				
Elasticated sound insulation underlay strips	SYL 250	352260	0	
DN 32 double-sphere rubber expansion joint	KOMP 32	362060	0	
Air-to-water heat pump connection kit	VSF 32	361800	0	
DN 32 dirt trap	SMF 32	362140	0	
Hydraulic accessories				
Transitional screw connection 1 1/4" internal thread to R 1"	KUP G32	375810	0	
Hydraulic tower 300 litres	HPK 300	371600	1	
Immersion heater 4.5 kW; ~400 V	CTHK 633	322140	0	
Immersion heater 6.0 kW; ~400 V	CTHK 634	322150	0	
Transport aid for Hydro-Tower / LAW indoor unit	TH 270	370430	0	
Free-standing buffer tank 200 l	PSW 200	339830	0	
Universal buffer tank (500 l)	PSW 500	339210	0	
Dual differential pressureless manifold	DDV 32	348450	0	
High-efficiency circulating pump DN 32 with coupling relay	UPH 90-32	370420	0	



Glen Dimplex Thermal Solutions
 (Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100
 Am Goldenen Feld 18 F: + 49 9221 709-339
 D-95326 Kulmbach dimplex@dimplex.de
 www.dimplex.de

Glen Dimplex Austria GmbH
 Hauptstraße 71
 A-5302 Henndorf am Wallersee

T: + 43 6214 20330
 F: + 43 6214 203304
 info@dimplex.at
 www.dimplex.at

Data sheet WI 22TU

Description	Order ref.	Article number	Sample item	Item
Manifold bar DN 32	VTB 32-2	374920	0	
Manifold bar DN 32	VTB 32-3	374930	0	
Domestic hot water module/unmixed heating circuit module	WWM 32	367800	0	
Mixed heating circuit module	MMH 32	367790	0	
Electronically controlled wet-running pump, self-regulating	UPE 100-32K	374730	0	
Mixer module for bivalent systems	MMB 32	367780	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-50	362520	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-100	362530	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-150	362540	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-200	362550	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-300	362560	0	
Immersion heater pipe assembly	HDLR 450	337450	0	
Heating accessories				
Heat pump heater heating/pассиве cooling, depth 21.5 cm	WPHK 2150140	381260	0	
Heat pump heater heating/pассиве cooling, depth 16.5 cm	WPHK 1650100	381220	0	
Heat pump heater heating/pассиве cooling, depth 21.5 cm	WPHK 2150180	381270	0	
Heat pump heater heating/pассиве cooling, depth 21.5 cm	WPHK 2150100	381250	0	
Heat pump heater vertical	WPHKV 1220053	381280	0	
Heat pump heater heating/pассиве cooling, depth 16.5 cm	WPHK 1650140	381230	0	
Heat pump heater heating/pассиве cooling, depth 16.5 cm	WPHK 1650180	381240	0	



Glen Dimplex Thermal Solutions
 (Glen Dimplex Deutschland GmbH) T: +49 9221 709-100
 Am Goldenen Feld 18 F: +49 9221 709-339
 D-95326 Kulmbach dimplex@dimplex.de
 www.dimplex.de

Glen Dimplex Austria GmbH
 Hauptstraße 71
 A-5302 Henndorf am Wallersee

T: +43 6214 20330
 F: +43 6214 203304
 info@dimplex.at
 www.dimplex.at

Data sheet WI 22TU

Description	Order ref.	Article number	Sample item	Item
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 165080	381210	0	
DHW preparation accessories				
Domestic hot water cylinder (500l) with temperature sensor	WWSP 556	370080	1	
FLH 25M flange heater	FLH 25M	349430	0	
Flange heater for domestic hot water	FLH 60	338060	0	
Flange heater for domestic hot water	FLHU 70	338070	0	
Safety valve combination	SVK 852	326660	0	
Domestic hot water cylinder, 700 litres	WWSP 770	376730	0	
3-way reversing valve DN 32	DWV 32	374780	0	
Pump unit DN 32 for direct connection of the domestic hot water cylinder	WPG 32	356040	0	
Control accessories				
Extension for an Ethernet network connection	NWPM Touch	378800	1	
Expansion module WPM for a KNX/EIB connection	KNX WPM	376350	0	
Extension for a Modbus RTU connection	LWPM 410	339410	0	



Glen Dimplex Thermal Solutions
 (Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100
 Am Goldenen Feld 18 F: + 49 9221 709-339
 D-95326 Kulmbach dimplex@dimplex.de
 www.dimplex.de

Glen Dimplex Austria GmbH
 Hauptstraße 71
 A-5302 Henndorf am Wallersee

T: + 43 6214 20330
 F: + 43 6214 203304
 info@dimplex.at
 www.dimplex.at

Data sheet WI 22TU

Description	Order ref.	Article number	Sample item	Item
Outside temperature sensor with casing	FG 3115	336620	0	
Temperature sensor NTC-10 with metal sleeve	NTC-10M	363600	0	
Accessories for passive cooling				
Plate heat exchanger for SIH 20	WTE 20	358400	0	
Control accessories (cooling)				
Room climate station for temperature and humidity measurement	RKS WPM	342220	0	
Dew point monitor	TPW WPM	350970	0	
Solar thermal systems accessories				
400l solar cylinder for heat pump	WWSP 432 SOL	361080	0	
500 l solar cylinder for heat pump	WWSP 540 SOL	361090	0	

* Other specific accessories available / required

Important information:

The combination of the components and the quantities indicated represent a non-binding sample system, which needs to be tested and individually adapted as required. Pump dimensioning must be reviewed according to the pressure loss of the system and the minimum heating water flow rate of the heat pump.



Glen Dimplex Thermal Solutions
 (Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100
 Am Goldenen Feld 18 F: + 49 9221 709-339
 D-95326 Kulmbach dimplex@dimplex.de
 www.dimplex.de

Glen Dimplex Austria GmbH
 Hauptstraße 71
 A-5302 Henndorf am Wallersee

T: + 43 6214 20330
 F: + 43 6214 203304
 info@dimplex.at
 www.dimplex.at